Job Name: Mark: Submitted By: Date: 12/05/2025

Centrifugal Downblast Exhaust Fan, Product # GB-130-3119XQD-DR2, 1011-1377 CFM

Model GB, belt drive centrifugal roof exhaust fans are designed to meet the general clean air exhaust requirements for industrial and commercial buildings. Units feature a fully rolled windband bead for increased stability and easy transport. Fresh outside air is drawn in under the motor cover to maximize motor life.

- •19 x 19 inch base with prepunched mounting holes for easy attachment to roof curb
- •Variable pitch adjustable motor pulley to optimize fan performance
- ●15.5 x 15.5 inch recommended roof opening

Certifications

AMCA Sound &Air High Wind and Hurricane Seismic UL/cUL 705

Performance Characteristics

No Fan Curve Available.

Construction Features

·				
Drive Type	Belt Drive			
Impeller Type	Centrifugal Wheel			
Impeller Material	Aluminum			
Housing Material	Spun Aluminum			
Includes	Unassembled drive package			
Certifications	AMCA Sound &Air			
Certifications	High Wind and Hurricane			
Certifications	Seismic			
Certifications	UL/cUL 705			
Drive Package Description	Motor and drives shipped			
	loose			
Required Accessory	Roof curb for new installations			

Motor Information

Service Factor	1.35
Phase	1
Voltage	115/208-230
HP	1/3
Motor Enclosure	Open Drip Proof
Motor Insulation	В
Thermal Protection	AutoOverload
NEMA Frame Size	48

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375
1/3 0.11 970	070	700	CFM	1,377	1,277	1,162	1,011	
	780	Sones	7.8	7.6	7.3	7		