Job Name: Mark: Submitted By: Date: 12/15/2025

Centrifugal Downblast Exhaust Fan, Product # G-120-A5119XQD, 1180-2093 CFM

Model G, direct drive centrifugal roof exhaust fans provide the industry's best performance and durability for general clean air applications where air is discharged downward, toward the roof. Units feature the most advanced motor cooling of any fan in its class.

- •19 x 19 inch base with prepunched mounting holes for easy attachment to roof curb
- •Speed controllable, with up to 30% turndown
- •15.5 x 15.5 inch recommended roof opening

Certifications

AMCA Sound &Air High Wind and Hurricane Seismic UL/cUL 705

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Direct Drive						
Impeller Type	Centrifugal Wheel						
Impeller Material	Aluminum						
Housing Material	Spun Aluminum						
Certifications	AMCA Sound &Air						
Certifications	High Wind and Hurricane						
Certifications	Seismic						
Certifications	UL/cUL 705						
Speed Controllable	Yes						
D : 14	Roof curbs for new						
Required Accessory	installations						

Motor Information

Service Factor	1
Phase	1
Voltage	115/230
HP	1/2
Motor Enclosure	Open Drip Proof
Motor Insulation	В
Thermal Protection	AutoOverload

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25	1.5
1/2 0.50	1705	0	CFM	2,093	2,038	1,984	1,928	1,871	1,810	1,743	1,673	1,600	1,426	1,180	
	0.50	0.50 1725	0	Sones	17.4	17.2	17.1	16.9	16.7	16.4	16.2	16	15.2	14.4	13.7

- •Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type A: Free inlet, Free outlet.
- •Power rating (BHP/kW) does not include transmission losses.
- •Performance ratings include the effects of birdscreen.
- •The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: free inlet hemispherical sone levels.