SKU GB-098-4119XQDR3

Job Name: Mark: Submitted By: Date: 10/21/2025

Centrifugal Downblast Exhaust Fan, Product # GB-098-4119XQDR3, 527-864 CFM



Model GB, belt drive centrifugal roof exhaust fans are designed to meet the general clean air exhaust requirements for industrial and commercial buildings. Units feature a fully rolled windband bead for increased stability and easy transport. Fresh outside air is drawn in under the motor cover to maximize motor life.

- •19 x 19 inch base with prepunched mounting holes for easy attachment to roof curb
- Variable pitch adjustable motor pulley to optimize fan performance
- •15.5 x 15.5 inch recommended roof opening


C C 134 inch

В

Certifications

AMCA Sound &Air High Wind and Hurricane Seismic UL/cUL 705

Performance Characteristics



Construction Features

Drive Type	Belt Drive
Impeller Type	Centrifugal Wheel
Impeller Material	Aluminum
Housing Material	Spun Aluminum
Includes	Assembled drive package
Includes	Disconnect switch
Certifications	AMCA Sound &Air
Certifications	High Wind and Hurricane
Certifications	Seismic
Certifications	UL/cUL 705
Drive Package Description	Motor and drives assembled
Required Accessory	Roof curb for new installations

Air and Sound Performance

Mo	tor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1
	1/4 0.19	0.10	1725	1200	CFM	864	829	793	756	719	679	640	592	527
		1725	25 1290	Sones	12.7	12.5	12.3	12.1	11.7	11.4	11.1	10.8	10.6	