Job Name: Mark: Submitted By: Date: 12/15/2025

Oscillating Air Circulator, Model ICO-24, 1/2HP, 115V, 1Ph, 4460-6400 CFM

Model ICO, oscillating circulator fans are designed for air movement in humid and demanding applications. Units are ideal for spot cooling and recirculating air in factories, warehouses, manufacturing facilities and garages. Units sweep through 45° or 90° arc. Mounting accessory sold separately.

- •Totally enclosed motor
- $\bullet_{Preassembled}$
- OSHA-compliant zinc plated wire guard
- •Circulator can sweep through 45° or 90° arc

Certifications

UL/cUL 507

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Direct Drive
Impeller Type	Propeller
Impeller Material	Aluminum
Includes	Mounting hardware
Includes	Power cord with 3-prong plug
Certifications	UL/cUL 507
Required Accessory	Mounting accessory

Motor Information

Service Factor	1
Phase	1
Voltage	115
HP	1/2
Motor Enclosure	Totally Enclosed Air Over
Motor Insulation	В
NEMA Frame Size	48YZ

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)
1/2 0.00	0.00	750	0	CFM
	0.00			Sones
1/2 0.00	0.00	1075	0	CFM
	0.00			Sones