Job Name: Mark: Submitted By: Date: 12/22/2025

# Inline-direct drive, VariGreen EC, insulation, 1/6HP 115V/1ph

Model CSP inline fans are high performance fans designed for exhaust, supply or return air applications where low sound level are required. Units feature an insulated, galvanized steel housing with a forward-curved wheel.

- •22.625 x 13.25 inch inlet width x height
- •17.4375 x 8 inch outlet width x height
- ulletSpeed controllable, with up to 30% turndown

#### Certifications

AMCA Air UL/cUL 507

## **Performance Characteristics**

No Fan Curve Available.

## **Construction Features**

Drive Type	Direct Drive
Impeller Type	Centrifugal Wheel
Impeller Material	Polypropylene
Housing Material	Galvanized Steel
Includes	Access Panel
Includes	Backdraft damper
Includes	Mounting brackets
Certifications	AMCA Air
Certifications	UL/cUL 507
Speed Controllable	Yes

## **Motor Information**

		_
Service Factor	1	
Phase	1	
Voltage	115	
Motor Enclosure	n/a	
Motor Insulation	В	
Thermal Protection	AutoOverload	
Watts	93	

## Air and Sound Performance

Watts	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5
335	950	760	CFM	908	841	782	715	631
			Sones	2	2	2.4	3	3.6