Job Name: Mark: Submitted By: Date: 09/10/2025

Centrifugal Inline Fan, Model BSQ-160, Belt Drive, 1/2HP, 208-230/460V, 3Ph, Motor & Drives Unassembled, 2094-3349 CFM




Model BSQ centrifugal inline fan features a unique combination of installation flexibility, rugged construction, ease of service, high efficiency and low sound levels. These compact fans are the ideal selection for indoor clean air applications including intake, exhaust, return or make-up air.


- •22.875 x 22.875 inch inlet width x height
- •22.875 x 22.875 inch outlet width x height
- •Horizontal or vertical mounting

Certifications

AMCA Sound &Air UL/cUL 705

Performance Characteristics





Construction Features

Drive Type	Belt Drive					
Impeller Type	Centrifugal Wheel					
Impeller Material	Aluminum					
Housing Material	Galvanized Steel					
Includes	Motor cover					
Includes	Unassembled drive package					
Certifications	AMCA Sound &Air					
Certifications	UL/cUL 705					
Drive Package Description	Motor and drives shipped loose					

Motor Information

Service Factor	1.25					
Phase	3					
Voltage	208-230/460					
HP	1/2					
Motor Enclosure	Open Drip Proof					
Motor Insulation	F					
NEMA Frame Size	56					

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1
1/2 0.61	1160	020	CFM	3,349	3,238	3,126	3,007	2,872	2,722	2,556	2,353	2,094	
	0.61	1160	1160 930	Sones	13.6	13.3	13	12.8	12.6	12.4	12.1	11.8	11.6



- •Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type B: Free inlet, Ducted outlet.
- •Power rating (BHP/kW) includes transmission losses.
- •Performance ratings do not include the effects of appurtenances (accessories).
- •The inlet sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type B: free inlet hemispherical sone levels.