

## SKU G-140-B3122XQD

Job Name: Mark: Submitted By: Date: 08/12/2025

# Centrifugal Downblast Exhaust Fan, Product # G-140-B3122XQD, 1233-2115 CFM




Model G, direct drive centrifugal roof exhaust fans provide the industry's best performance and durability for general clean air applications where air is discharged downward, toward the roof. Units feature the most advanced motor cooling of any fan in its class.


- •22 x 22 inch base with prepunched mounting holes for easy attachment to roof curb
- •Speed controllable, with up to 30% turndown
- •18.5 x 18.5 inch recommended roof opening

### Certifications

AMCA Sound &Air High Wind and Hurricane Seismic UL/cUL 705



#### **Performance Characteristics**



#### **Construction Features**

Drive Type	Direct Drive				
Impeller Type	Centrifugal Wheel				
Impeller Material	Aluminum				
Housing Material	Spun Aluminum				
Certifications	AMCA Sound &Air				
Certifications	High Wind and Hurricane				
Certifications	Seismic				
Certifications	UL/cUL 705				
Speed Controllable	Yes				
D : 1.4	Roof curbs for new				
Required Accessory	installations				

## **Motor Information**

Service Factor	1
Phase	1
Voltage	115
HP	1/3
Motor Enclosure	Open Drip Proof
Motor Insulation	В
Thermal Protection	AutoOverload

## Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75
1/3 0.31	0.21	1140	0	CFM	2,115	2,008	1,905	1,792	1,660	1,488	1,233
	0.31			Sones	11.2	11	10.5	10.1	9.6	9	8.4



- •Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type A: Free inlet, Free outlet.
- •Power rating (BHP/kW) does not include transmission losses.
- •Performance ratings include the effects of birdscreen.
- •The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: free inlet hemispherical sone levels.