Job Name: Mark: Submitted By: Date: 11/10/2025

# Centrifugal Inline Fan, Model BSQ-160, Belt Drive, 1 1/2HP, 115/208-230V, 1Ph, Motor & Drives Unassembled, 3120-4822 CFM




Model BSQ centrifugal inline fan features a unique combination of installation flexibility, rugged construction, ease of service, high efficiency and low sound levels. These compact fans are the ideal selection for indoor clean air applications including intake, exhaust, return or make-up air.


- •22.875 x 22.875 inch inlet width x height
- •22.875 x 22.875 inch outlet width x height
- •Horizontal or vertical mounting

#### Certifications

AMCA Sound &Air UL/cUL 705

## **Performance Characteristics**





#### Construction Features

Drive Type	Belt Drive							
Impeller Type	Centrifugal Wheel							
Impeller Material	Aluminum							
Housing Material	Galvanized Steel							
Includes	Motor cover							
Includes	Unassembled drive package							
Certifications	AMCA Sound &Air							
Certifications	UL/cUL 705							
Drive Package Description	Motor and drives shipped loose							

## **Motor Information**

Phase	1
Voltage	115/208-230
HP	1 1/2
Motor Enclosure	Open Drip Proof
Motor Insulation	В

Thermal Protection AutoOverload

### Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25	1.5	1.75	2
1 1/2	1.83	1670	1340	CFM	4,822	4,744	4,667	4,590	4,512	4,435	4,349	4,256	4,162	3,958	3,740	3,462	3,120
				Sones	26	25	24	24	24	24	24	24	24	23	22	20	18.5



- •Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type B: Free inlet, Ducted outlet.
- •Power rating (BHP/kW) includes transmission losses.
- •Performance ratings do not include the effects of appurtenances (accessories).
- •The inlet sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type B: free inlet hemispherical sone levels.