


Centrifugal Upblast Exhaust Fan, Product # CUBE-140-5122G3QD-DR4, 1354-2608 CFM



The CUBE is an aluminum exhaust fan specifically designed for roof or sidewall mounted applications where contaminated or grease laden exhaust air can be discharged directly upward, away from the roof or wall surface. The fans feature a one piece windband continuously welded to curb cap and double studded isolators for true vibration isolation.


- 22 x 22 inch base with prepunched mounting holes for easy attachment to roof curb
- 18.5 x 18.5 inch recommended roof opening
- Roof or wall mountable



Certifications

AMCA Sound & Air
 UL/cUL 705 Listed - Supplement SC - "Power
 Ventilators for Restaurant Exh. Appliances" (Formerly
 UL 762)

Performance Characteristics



Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25
1/2	0.58	1440	1160	CFM	2,608	2,538	2,459	2,372	2,281	2,183	2,073	1,948	1,802	1,354
				Sones	16	15.5	15.2	14.2	13.2	12.07	12.2	11.9	11.4	10.1

Construction Features

Drive Type	Belt Drive
Impeller Type	Centrifugal Wheel
Impeller Material	Aluminum
Housing Material	Spun Aluminum
Includes	Unassembled drive package
Certifications	AMCA Sound & Air UL/cUL 705 Listed - Supplement SC - "Power Ventilators for Restaurant Exh. Appliances" (Formerly UL 762)
Certifications	Motor and drives shipped loose
Drive Package Description	Roof curb for new roof installations
Required Accessory	

Motor Information

Service Factor	1.25
Phase	3
Voltage	208-230/460
HP	1/2
Motor Enclosure	Open Drip Proof
Motor Insulation	F
NEMA Frame Size	56