Job Name: Mark: Submitted By: Date: 12/15/2025

# Centrifugal Supply Fan, Model SAF-112, Belt Drive, Less Motor & Drive Package, 1710-4219 CFM

Model SAF is a filtered supply fan designed to provide non-tempered make-up air to commercial or industrial buildings, including commercial kitchen applications. Fresh outdoor air is supplied to replace air lost through hood exhaust or general building ventilation.

- •34.5 x 34.5 inch base with prepunched mounting holes for easy attachment to roof curb
- Multiple motor and drive options available to meet any performance and application need
- •20.5 x 20.5 inch recommended roof opening

## Certifications

AMCA Sound &Air UL/cUL 705

### **Performance Characteristics**

No Fan Curve Available.

## **Construction Features**

| Drive Type                | Belt Drive                |  |  |  |  |  |
|---------------------------|---------------------------|--|--|--|--|--|
| Impeller Type             | Forward Curved Wheel      |  |  |  |  |  |
| Impeller Material         | Aluminum                  |  |  |  |  |  |
| Housing Material          | Galvanized Steel          |  |  |  |  |  |
| Includes                  | Access Panels             |  |  |  |  |  |
|                           | Washable, aluminum 1-inch |  |  |  |  |  |
| Includes                  | filters                   |  |  |  |  |  |
| Certifications            | AMCA Sound &Air           |  |  |  |  |  |
| Certifications            | UL/cUL 705                |  |  |  |  |  |
| Drive Package Description | No drive package included |  |  |  |  |  |
| D : 14                    | Roof curb for new roof    |  |  |  |  |  |
| Required Accessory        | installations             |  |  |  |  |  |

## **Motor Information**

| Motor Included | No |
|----------------|----|
|----------------|----|

## Air and Sound Performance

| Motor HP | Max BHP | Max Fan<br>RPM | Min Fan<br>RPM | Ps (in. wg) | 0     | 0.125 | 0.25  | 0.375 | 0.5   | 0.625 | 0.75  |
|----------|---------|----------------|----------------|-------------|-------|-------|-------|-------|-------|-------|-------|
| 1/2      | 0.50    | 610            | 490            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 1/2      | 0.50    | 610            | 490            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 3/4      | 0.76    | 700            | 590            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 3/4      | 0.76    | 700            | 590            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 1        | 1.01    | 770            | 630            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 1        | 1.01    | 1.01 770       | 630            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 1 1/2    | 1.51    | 880            | 740            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |
| 1 1/2    | 1.51    | 880            | 740            | CFM         | 2,862 | 2,562 | 2,214 | 1,710 | 1,944 | 2,044 | 2,538 |
|          |         |                |                | Sones       | 18    | 16.2  | 14.7  | 12    | 15.5  | 17.8  | 19.7  |