SKU CUBE-240-LMD134GQD

Job Name: Mark: Submitted By: Date: 11/25/2025

Centrifugal Upblast Exhaust Fan, Model CUBE-240, Belt Drive, Less Motor & Drive Package, 2639-8431 CFM

The CUBE is an aluminum exhaust fan specifically designed for roof or sidewall mounted applications where contaminated or grease laden exhaust air can be discharged directly upward, away from the roof or wall surface. The fans feature a one piece windband continuously welded to curb cap and double studded isolators for true vibration isolation.

- •34 x 34 inch base with prepunched mounting holes for easy attachment to roof curb
- Multiple motor and drive options available to meet any performance and application need
- •30.5 x 30.5 inch recommended roof opening

Certifications

AMCA Sound &Air UL/cUL 705 Listed - Supplement SC - "Power Ventilators for Restaurant Exh. Appliances" (Formerly UL 762)

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Belt Drive						
Impeller Type	Centrifugal Wheel						
Impeller Material	Aluminum						
Housing Material	Spun Aluminum						
Includes	Disconnect switch						
Certifications	AMCA Sound &Air						
	UL/cUL 705 Listed -						
	Supplement SC - "Power						
Certifications	Ventilators for Restaurant Exh						
	Appliances" (Formerly UL						
	762)						
Drive Package Description	No drive package included						
	Roof curb for new roof						
Required Accessory	installations						

Motor Information

Motor Included	No	

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25	1.5
1/4	1/4 0.29	480	410	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1/4				Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1/2	1/3 0.21	430	410	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1/3				Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1/3	0.20	530	430	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1/3	0.39			Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1/2	1/2 0.31	490	410	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1/2				Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1/0 0.50	(10	400	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324	
1/2	1/2 0.59	610	490	Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
3/4	0.46	560	490	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
3/4	0.46) 480	Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
2/4	0.96	690	5.00	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
3/4	0.86		560	Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1	1 15	760	(10	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1	1 1.15		760 610	Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1 1/0	0.00	90 700	0 600	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1 1/2 0.90	0.90			Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
1.1/2	1.1/0 1.70	870	700	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
1 1/2 1.72	1.72			Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
2	1.10	750	690	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
2	1.10	750		Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18
2 2.10	2.10	930	750	CFM	4,352	3,928	3,370	2,639	3,902	3,156	3,991	4,526	3,555	4,670	4,324
	930	930 /30	Sones	8.2	7.4	6.8	6.4	9.3	8.8	11.4	14	13.6	16.1	18	

- ullet Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal.
- •The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type A: Free inlet, Free outlet.
- •Power rating (BHP/kW) includes transmission losses.
- •Performance ratings do not include the effects of appurtenances (accessories).
- •The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: free inlet hemispherical sone levels.