Job Name: Mark: Submitted By: Date: 12/05/2025

Centrifugal Downblast Exhaust Fan, Product # GB-140-3122XQD-DR3, 1167-1799 CFM

Model GB, belt drive centrifugal roof exhaust fans are designed to meet the general clean air exhaust requirements for industrial and commercial buildings. Units feature a fully rolled windband bead for increased stability and easy transport. Fresh outside air is drawn in under the motor cover to maximize motor life.

- •22 x 22 inch base with prepunched mounting holes for easy attachment to roof curb
- •Variable pitch adjustable motor pulley to optimize fan performance
- •18.5 x 18.5 inch recommended roof opening

Certifications

AMCA Sound &Air High Wind and Hurricane Seismic UL/cUL 705

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Belt Drive			
Impeller Type	Centrifugal Wheel			
Impeller Material	Aluminum			
Housing Material	Spun Aluminum			
Includes	Unassembled drive package			
Certifications	AMCA Sound &Air			
Certifications	High Wind and Hurricane			
Certifications	Seismic			
Certifications	UL/cUL 705			
Drive Package Description	Motor and drives shipped			
	loose			
Required Accessory	Roof curb for new installations			

Motor Information

Service Factor	1.35
Phase	1
Voltage	115/208-230
HP	1/3
Motor Enclosure	Open Drip Proof
Motor Insulation	В
Thermal Protection	AutoOverload
NEMA Frame Size	48

Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5
1/3	0.10	970	780	CFM	1,799	1,676	1,550	1,395	1,167
	0.19			Sones	8.5	8.4	8	7.5	7