### SKU CUBE-240-4134GQD-DR1

Job Name: Mark: Submitted By: Date: 12/14/2025

# Centrifugal Upblast Exhaust Fan, Model CUBE-240, Belt Drive, 1/4HP, 115V, 1Ph, Motor & Drives Unassembled, 2639-4352 CFM

The CUBE is an aluminum exhaust fan specifically designed for roof or sidewall mounted applications where contaminated or grease laden exhaust air can be discharged directly upward, away from the roof or wall surface. The fans feature a one piece windband continuously welded to curb cap and double studded isolators for true vibration isolation.

- •34 x 34 inch base with prepunched mounting holes for easy attachment to roof curb
- •30.5 x 30.5 inch recommended roof opening
- •Roof or wall mountable

#### Certifications

AMCA Sound &Air UL/cUL 705 Listed - Supplement SC - "Power Ventilators for Restaurant Exh. Appliances" (Formerly UL 762)

#### **Performance Characteristics**

No Fan Curve Available.

#### **Construction Features**

Drive Type	Belt Drive			
Impeller Type	Centrifugal Wheel			
Impeller Material	Aluminum			
Housing Material	Spun Aluminum			
Includes	Unassembled drive package			
Certifications	AMCA Sound &Air			
	UL/cUL 705 Listed -			
	Supplement SC - "Power			
Certifications	Ventilators for Restaurant Exh.			
	Appliances" (Formerly UL			
	762)			
D: D1 D :	Motor and drives shipped			
Drive Package Description	loose			
<b>5</b>	Roof curb for new roof			
Required Accessory	installations			

## Air and Sound Performance

	Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375
1/4	0.29	400	410	CFM	4,352	3,928	3,370	2,639	
		480	410	Sones	8.2	7.4	6.8	6.4	

- •Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal.
- •The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type A: Free inlet, Free outlet.
- •Power rating (BHP/kW) includes transmission losses.
- •Performance ratings do not include the effects of appurtenances (accessories).
- •The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: free inlet hemispherical sone levels.