Job Name: Mark: Submitted By: Date: 01/05/2026

Ceiling Exhaust Fan, Model SP-A1050, 115V, 1Ph, 662-1125 CFM

Model SP-A direct drive, ceiling mounted fan is designed to provide the lowest sounds levels for bathroom exhaust. Units feature an insulated housing and are ideal for residential, multi-family or hotel applications.

- Acoustic insulation absorbs sound ensuring quiet operation
- •Spring loaded aluminum backdraft damper eliminates rattling
- •External electrical access reduces installation time
- •Speed controllable
- •Designer grille included

Certifications

AMCA Air &Sound UL/cUL 507

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Direct Drive			
Impeller Type	Centrifugal Wheel			
Impeller Material	Polypropylene			
Housing Material	Galvanized Steel			
Includes	Backdraft damper			
Includes	Mounting brackets			
Certifications	AMCA Air &Sound			
Certifications	UL/cUL 507			
Speed Controllable	Yes			

Motor Information

Service Factor	1
Phase	1
Voltage	115
Motor Enclosure	n/a
Motor Insulation	В
Thermal Protection	AutoOverload
Watts	190

Air and Sound Performance

	Watts	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625
	1005	076	CFM	1,125	1,043	964	885	796	662	
	420	1095	876	Sones	6	6	6	5.5	5.5	5.5