

### SKU GB-300-30140X3QD-DR2

Job Name: Mark: Submitted By: Date: 11/09/2025

# Centrifugal Downblast Exhaust Fan, Model GB-300, Belt Drive, 3HP, 208-230/460V, 3Ph, Motor & Drives Unassembled, 6864-12473 CFM



Model GB, belt drive centrifugal roof exhaust fans are designed to meet the general clean air exhaust requirements for industrial and commercial buildings. Units feature a fully rolled windband bead for increased stability and easy transport. Fresh outside air is drawn in under the motor cover to maximize motor life.


- •40 x 40 inch base with prepunched mounting holes for easy attachment to roof curb
- Variable pitch adjustable motor pulley to optimize fan performance
- •36.5 x 36.5 inch recommended roof opening

# B C C 1¾ inch

### Certifications

AMCA Sound &Air High Wind and Hurricane Seismic UL/cUL 705

# **Performance Characteristics**



### **Construction Features**

Drive Type	Belt Drive					
Impeller Type	Centrifugal Wheel					
Impeller Material	Aluminum					
Housing Material	Spun Aluminum					
Includes	Unassembled drive package					
Certifications	AMCA Sound &Air					
Certifications	High Wind and Hurricane					
Certifications	Seismic					
Certifications	UL/cUL 705					
5. 5. 5	Motor and drives shipped					
Drive Package Description	loose					
Required Accessory	Roof curb for new installations					

# **Motor Information**

Service Factor	1.15
Phase	3
Voltage	208-230/460
HP	3
Motor Enclosure	Open Drip Proof
Motor Insulation	F
NEMA Frame Size	182T

# Air and Sound Performance

Motor HP	Max BHP	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0	0.125	0.25	0.375	0.5	0.625	0.75	0.875	1	1.25	1.5	
3 3.29	2.00	29 770	770	620	CFM	12,473	12,173	11,873	11,535	11,180	10,817	10,440	10,039	9,596	8,556	6,864
	3.29			620	Sones	23	23	22	22	21	21	21	19 9	19 3	17.7	15.4



- •Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.
- •Performance certified is for installation type A: Free inlet, Free outlet.
- •Power rating (BHP/kW) includes transmission losses.
- •Performance ratings include the effects of birdscreen.
- •The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: free inlet hemispherical sone levels.